

# theFAN™

The best complement to any atmospheric effect

Designed to work in tandem with our professional generators or as a stand alone unit, theFAN™ is a versatile, 100W, ultra-compact, variable speed, digital fan.



## FEATURES

- Variable speed and air flow up to 850 CFM
- Free standing or variable mounting options
- Universal switching power supply 100 - 250 VAC, 50/60 Hz, single phase
- Noise Level at 1 m (3.3'): 64db at maximum speed
- 4 buttons LCD user interface, USITT DMX512, XLR-5 connectors, RDM compliant
- One-channel standard mode or two-channel quiet mode

## TECHNICAL DATA

<b>Mechanical</b>	<ul style="list-style-type: none"> <li>• 3-bladed fan</li> <li>• 270° tilt</li> <li>• Variable speed</li> <li>• Airflow: 850 CFM</li> <li>• Noise Level: 64db at full speed</li> <li>• Omega clamp socket</li> <li>• M12 metric bolt hole</li> </ul>	<ul style="list-style-type: none"> <li>• 0.5" imperial bolt hole</li> <li>• 2 handles</li> <li>• 4-button controller with LCD panel</li> <li>• Total net weight: 6.8kg (15 lb)</li> <li>• Total net size: 38 cm (15") H x 34.5 cm (13.95") W x 25.4 cm (10") D</li> <li>• Fan diameter: 26.4 cm (10.4")</li> </ul>
<b>Electrical</b>	<ul style="list-style-type: none"> <li>• 100 - 250 VAC, 50/60 Hz, single phase</li> <li>• 100 Watts</li> </ul>	
<b>Data</b>	<ul style="list-style-type: none"> <li>• 1 standard USITT DMX512 channel</li> <li>• 2 XLR-5 connectors: 1 input, 1 output</li> <li>• Controllable through DMX + RDM</li> </ul>	
<b>Digital Functions</b>	<ul style="list-style-type: none"> <li>• Stand alone set speed</li> <li>• DMX Value</li> </ul>	
<b>Accessories</b>	Flight case	
<b>Approval</b>	CE certified, CSA and UL approved	